

# Wall mounted unit

FTXP-K3 / RXP-K3



Energy saving during standby mode



Online controller via app



Multi model application

## Discreet wall mounted unit providing high efficiency and comfort

- › Whisper quiet in operation down to 20 dBA
  - › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
  - › Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency

# FTXP-K3 / RXP-K3



Indoor unit		FTXP	20K3	25K3	35K3	50K3	60K3	71K3	
Casing	Colour		White						
Dimensions	Unit	HeightxWidthxDepth	286x770x225			295x990x263			
Sound power level	Cooling	dBA	55		58	59	60	62	
	Heating	dBA	55		58	61	62		
Sound pressure level	Cooling	High/Low/Silent operation	dBA	39/25/20	40/26/20	43/27/20	43/34/31	45/36/33	46/37/34
	Heating	High/Low/Silent operation	dBA	39/28/21	40/28/21	40/29/21	42/33/30	44/35/32	45/36/33
Control systems	Infrared remote control		ARC480A11						
	Wired remote control		BRC944B2 / BRC073A1						

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.


Efficiency data			FTXP + RXP	20K3 + 20K3	25K3 + 25K3	35K3 + 35K3	50K3 + 50K3	60K3 + 60K3	71K3 + 71K3
Cooling capacity	Nom.		kW	2.00	2.50	3.50	5.0	6.0	7.1
Heating capacity	Nom.		kW	2.50	3.00	4.00	6.0	7.0	8.2
Power input	Cooling	Nom.	kW	0.50	0.65	1.01	1.390	1.820	2.690
	Heating	Nom.	kW	0.52	0.69	1.00	1.580	1.930	2.570
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class		A++					
		Pdesign	kW	2.00	2.50	3.50	5.00	6.00	7.10
		SEER		6.79	6.92	6.64	6.72	6.82	5.30
	Annual energy consumption		kWh	103	126	185	260	308	469
	Heating (Average climate)	Energy efficiency class		A+					
Pdesign		kW	2.20	2.40	2.80	4.60	4.80	6.20	
SCOP/A			4.65	4.61	4.64	4.10		3.81	
Annual energy consumption		kWh	662	728	845	1,571	1,640	2,279	
Nominal efficiency	EER		4.02	3.83	3.48	3.61	3.29	2.64	
	COP		4.77	4.36	4.02	3.80	3.63	3.19	
	Annual energy consumption		kWh	-					
	Energy labeling Directive	Cooling		A					
Heating			A						

Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m.

Outdoor unit			RXP	20K3	25K3	35K3	50K3	60K3	71K3
Dimensions	Unit	HeightxWidthxDepth	mm	550x765x285			735x825x300		734x870x320
Sound power level	Cooling	dBA	60	62		61	63	66	
	Heating	dBA	61	62		61	63	65	
Sound pressure level	Cooling	High	dBA	46	48		47	49	52
	Heating	High	dBA	47	48		49		52
Operation range	Cooling	Ambient	Min.-Max.	---					
Refrigerant	Type/Charge/GWP	kg/TCO <sub>2</sub> eq	R-32/0.76/0.52/675				R-32/1.40/0.95/675.0	R-32/1.45/0.98/675.0	R-32/1.15/0.78/675.0
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

ECPEN17-828

03/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.