

# Wall mounted unit

FTXP-L + RXP-L



Energy saving during standby mode



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Whisper quiet
- › Online controller (optional)
- › Ideal for above door installation
- › Bluevolution range: lower environmental impact

- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

# FTXP-L + RXP-L




Efficiency data		FTXP + RXP	20L + 20L	25L + 25L	35L + 35L	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	
Power input	Cooling	Min./Nom./Max.	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	
	Heating	Min./Nom./Max.	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	
Space cooling	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.00	2.50	3.50
	SEER			6.79	6.92	6.62
	Annual energy consumption		kWh/a	104	127	186
Space heating (Average climate)	Energy efficiency class		A++			
	Capacity	Pdesign	kW	2.20	2.40	2.80
	SCOP/A			4.65	4.61	4.64
	Annual energy consumption		kWh/a	662	728	845
Nominal efficiency	EER		4.02			
	COP		4.77			
	Energy labeling Directive	Cooling/Heating	A/A			

Indoor unit		FTXP	20L	25L	35L		
Dimensions	Unit HeightxWidthxDepth	mm	286x770x225				
Weight	Unit	kg	9.00				
Air filter	Type	Removable / washable					
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m <sup>3</sup> /min	4.4/5.9/7.9 / 9.8	4.4/6.1/8.1 / 10.1	4.5/6.3/8.3 / 11.5
		Heating	Silent operation/Low/Medium/High	m <sup>3</sup> /min	5.3/6.5/8.4 / 10.3	5.3/6.7/8.6 / 10.3	5.3/7.0/9.0 / 11.5
Sound power level	Cooling			55	58		
	Heating			55	58		
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20/25/39	20/26/40	20/27/43	
	Heating	Silent operation/Low/High	dBA	21/28/39	21/28/40	21/29/40	
Control systems	Infrared remote control		ARC480A11				
	Wired remote control		BRC944B2 / BRC073A1				
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240				

Outdoor unit		RXP	20L	25L	35L
Dimensions	Unit HeightxWidthxDepth	mm	550x658x275		
Weight	Unit	kg	28		
Sound power level	Cooling			60	62
	Heating			61	62
Sound pressure level	Cooling	High	dBA	46	48
	Heating	High	dBA	47	48
Operation range	Cooling	Ambient	Min.~Max.	°CDB -10~-46	
	Heating	Ambient	Min.~Max.	°CWB -15~-18	
Refrigerant	Type		R-32		
	GWP		675.0		
	Charge		kg/TCO2Eq	0.70/0.48	
Piping connections	Liquid	OD	mm	6,35	
	Gas	OD	mm	9,5	
	Piping length	OU - IU	Max.	m 15	
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m 12	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)	A	-		

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN18-046 01/2018



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.