







Solar ready

Enhanced hot water comfort

- > Quiet operation: with 53 dBA, one of the most silent products in its kind
- > Easy handling: thanks to its compact size, it can easily pass through the doorway
- > Enhanced comfort: the 3 operating modes will give an answer to all your needs
- > Solar connectivity: empower your house with renewable energy
- Wide operation range: down to -7 °C outside temperature with the heat pump, below -7 °C electrical heating element support



EKHH2E-PAV3



Single Unit				EKHH	2E260PAV3
COP					3.10 (1) / 3.60 (2)
Heat pump	Casing	Colour			White body / grey top
		Material			Cover: EPP top finishing
	Operation range	Ambient	Min.	°CDB	-7
			Max.	°CDB	38
	Power supply	Phase			1P
		Frequency	,	Hz	50
		Voltage		V	230
Tank	Casing	Colour			White
		Material			Embossed ABS
	Dimensions	Unit	Height	mm	1,500
	Operation range	Water side	Min.	°C	10
			Max.	°C	56
	Standing heat loss			W	71
	Power supply	Phase			1P
		Frequency	,	Hz	50
		Voltage		V	230

⁽¹⁾ Test at Ta DB/WB 7°C/6°C. According to EN 16147. (2) Test at Ta DB/WB 15°C/12°C. According to EN 16147.









ECPEN18-781



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet.

All content is copyrighted by Daikin Europe N.V.